



ARMoured RESCUE VEHICLE SPECS

CHASSIS / POWERTRAIN

Chassis: International 7400 SFA 4X4
Engine: Maxx Force DT, 285 HP Turbo
Torque: 800 lb-ft Torque @ 1400, 2400 RPM
Transmission: Allison 3500 EVS
Wheelbase: 163 inches
Turning Radius: 25 ft 6 in (51 ft diameter)

CAPACITIES

GVWR: 35 000 lbs
Front Axle: Meritor 12000 lbs
Rear Axle: Meritor 23000 lbs
Curb Weight: 28 000 lbs
Payload: 7 000 lbs
Fuel tank: 50 US gal



PERFORMANCES

Max speed: 128 km/h (80 mph)
0-60 km/h: 16 seconds
Approach Angle: 65 deg
Departure Angle: 30 deg

TIRES / RIMS

Basic: 11R22.5 with run flat
Optional: Michelin XZL 395 85R20
Hutchinson alu. rims with run flat

INTERIOR

Front Seats: Air ride GSS seat with 5 pt seatbelt
Mid Seats: 2 flip seats facing forward, 3 pt seatbelts
Rear Seats: 6 flip seats facing sideways, lap belt
Dual AC/heater: Red Dot
Auxiliary Heat: Espar D2 diesel fired heater 7500 btu/hr